

# DMX MERGER SPLITTER

- Can be used for merging information from two separate DMX signals in one.




Designed & Manufactured  
by ELECTRON SA

Code: **DEM.046**

## Features – Technical specifications.

- Two DMX-512 inputs.
- Two optical isolated outputs.
- Optical isolation between two outputs.
- Four operating modes (HTP, LAST, BACKUP, MERGE).
- Dip switches for start address selection.
- Dip switch for DMX signal termination on each input.
- Connection up to 25 devices on each output port.
- Two XLR 5-pin male plugs for DMX input connection.
- Two XLR 5-pin female plugs for DMX output connection.
- Power supply: 230VAC 50/60Hz.
- Power consumption: 2W
- Ambient temperature: -20 / +50oC.



# DMX REPEATER

- Can be used for expansion or/and branching of DMX network.



Designed & Manufactured  
by ELECTRON SA

Code: **DEM.045**

## Features – Technical specifications.

- DMX signal amplification.
- Input output optical isolation.
- Input signal termination capability.
- Connection up to 25 devices in output port.
- Capable of up to 5 Repeaters in series connection.
- Power supply: 230VAC 50/60Hz.
- Power consumption: 1,8 W
- Ambient temperature : -20 / +50oC.
- 0,5-2,5mm<sup>2</sup> screw terminals, for DMX input and output cable connection.
- Dimensions: L x W x H: 125mm x 68,5mm x 42,5mm.

