

# JOY SURFACE

**Monochromatic:** Management through:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Linear LED lighting available with satin square or satin round cover.
- Special design and construction to meet the most demanding lighting designs.
- L70 50.000h
- IP40



LIGHTSOURCE BY  
**NICHIA**



| Model                  | Luminaire Colour                          | Colour Temperature | Colour Rendering | Type                                  | Watt / Length          | Voltage       |
|------------------------|---|--------------------|------------------|---------------------------------------|------------------------|---------------|
| JOY SURFACE<br>(JOY S) | (AN) Anodized<br>(WH) White<br>(BL) Black | (20) 2000K         | (80) ≥ 80        | (SS) Satin Square<br>(SR) Satin Round | (07W035) 7W / 35cm     | 24VDC<br>(24) |
|                        |   | (25) 2500K         |                  |                                       | (12W060) 12.2W / 60cm  |               |
|                        |   | (27) 2700K         |                  |                                       | (17W085) 17.5W / 85cm  |               |
|                        |   | (30) 3000K         |                  |                                       | (21W102) 21W / 102cm   |               |
|                        |   | (40) 4000K         |                  |                                       | (24W119) 24.5W / 119cm |               |
|                        |   | (57) 5700K         |                  |                                       | (31W152) 31.5W / 152cm |               |
|                        |   |                    |                  |                                       | (42W202) 42W / 202cm   |               |

Ordering Code Example:

JOY S - AN - 40 - 80 - SR - 31W152 - 24

**Available upon request:**

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version



**Monochromatic:** Management through:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Pendant linear LED with satin square or satin round cover.
- Available with different CCT to meet all the architectural needs.
- L70 50,000h
- IP40



LIGHTSOURCE BY  
**NICHIA**

| Model                   | Luminaire Colour                          | Colour Temperature | Colour Rendering | Type                                  | Watt / Length          | Voltage       |
|-------------------------|---|--------------------|------------------|---------------------------------------|------------------------|---------------|
| JOY PENDANT<br>(JOY PD) | (AN) Anodized<br>(WH) White<br>(BL) Black | (20) 2000K         | (80) ≥ 80        | (SS) Satin Square<br>(SR) Satin Round | (07W035) 7W / 35cm     | 24VDC<br>(24) |
|                         |   | (25) 2500K         |                  |                                       | (12W060) 12.2W / 60cm  |               |
|                         |   | (27) 2700K         |                  |                                       | (17W085) 17.5W / 85cm  |               |
|                         |   | (30) 3000K         |                  |                                       | (21W102) 21W / 102cm   |               |
|                         |   | (40) 4000K         |                  |                                       | (24W119) 24.5W / 119cm |               |
|                         |   | (57) 5700K         |                  |                                       | (31W152) 31.5W / 152cm |               |
|                         |   |                    |                  |                                       | (42W202) 42W / 202cm   |               |

Ordering Code Example:  
JOY PD - AN - 40 - 80 - SR - 31W152 - 24

**Available upon request:**

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version

