



GU10 LED LAMPS

REFLED ES50 V2

SYLVANIA

Lifespan
(L70)
15.000ENERGY
CLASS
A+CRI
min80+

Code	Description	Lamp Holder	Watt	Equivalence	Voltage (50/60Hz)	CCT	Luminus Flux	Current	Beam Angle	Dimmable
LED.344	REFLED ES50 V2	GU10	5W	50W	220-240VAC	2700K	345lm	25mA	36°	NO
LED.264	REFLED ES50 V2	GU10	5W	50W	220-240VAC	3000K	345lm	25mA	36°	NO
LED.270	REFLED ES50 V2	GU10	6W	50W	220-240VAC	3000K	345lm	29mA	36°	YES
LED.345	REFLED ES50 V2	GU10	5W	50W	220-240VAC	4000K	345lm	25mA	36°	NO
LED.346	REFLED ES50 V2	GU10	6W	50W	220-240VAC	4000K	345lm	29mA	36°	YES
LED.347	REFLED ES50 V2	GU10	5W	50W	220-240VAC	6500K	345lm	25mA	36°	NO

REFLED + ES50 V2

SYLVANIA

Lifespan
(L70)
25.000ENERGY
CLASS
A+CRI
min80+

Code	Description	Lamp Holder	Watt	Equivalence	Voltage (50/60Hz)	CCT	Luminus Flux	Current	Beam Angle	Dimmable
LED.348	REFLED + ES50 V2	GU10	5.5W	53W	220-240VAC	2700K	360lm	30mA	40°	YES
LED.349	REFLED + ES50 V2	GU10	5.5W	53W	220-240VAC	3000K	370lm	30mA	40°	YES
LED.350	REFLED + ES50 V2	GU10	5.5W	53W	220-240VAC	4000K	380lm	30mA	40°	YES
LED.351	REFLED + ES50 V2	GU10	8W	83W	220-240VAC	2700K	600lm	37mA	40°	YES
LED.352	REFLED + ES50 V2	GU10	8W	83W	220-240VAC	3000K	600lm	37mA	40°	YES
LED.353	REFLED + ES50 V2	GU10	8W	83W	220-240VAC	4000K	600lm	37mA	40°	YES

REFLED COOLFIT ES50 DIM

SYLVANIA

Lifespan
(L70)
25.000ENERGY
CLASS
A+CRI
min80+

Code	Description	Lamp Holder	Watt	Equivalence	Voltage (50/60Hz)	CCT	Luminus Flux	Current	Beam Angle	Dimmable
LED.354	REFLED COOLFIT ES50 DIM	GU10	5.5W	50W	220-240VAC	2700K	345lm	30mA	25°	YES
LED.355	REFLED COOLFIT ES50 DIM	GU10	5.5W	50W	220-240VAC	2700K	345lm	30mA	40°	YES
LED.356	REFLED COOLFIT ES50 DIM	GU10	5.5W	50W	220-240VAC	3000K	345lm	30mA	25°	YES
LED.357	REFLED COOLFIT ES50 DIM	GU10	5.5W	50W	220-240VAC	3000K	345lm	30mA	40°	YES
LED.358	REFLED COOLFIT ES50 DIM	GU10	5.5W	50W	220-240VAC	4000K	345lm	30mA	40°	YES



MR16 LED LAMPS


REFLED MR16 V2



Lifespan
(L70)
15.000

ENERGY
CLASS
A+

CRI
min80+

Code	Description	Lamp Holder	Watt	Equivalence	Voltage (50/60Hz)	CCT	Luminus Flux	Current		Dimmable
LED.359	REFLED MR16 V2	GU5.3	5.5W	35W	12V	2700K	345lm	650mA	36°	NO
LED.360	REFLED MR16 V2	GU5.3	5.5W	35W	12V	3000K	345lm	650mA	36°	NO
LED.361	REFLED MR16 V2	GU5.3	5.5W	35W	12V	4000K	345lm	650mA	36°	NO




REFLED SUPERIA MR16



Lifespan
(L70)
25.000

ENERGY
CLASS
A+

CRI
min80+

Code	Description	Lamp Holder	Watt	Equivalence	Voltage (50/60Hz)	CCT	Luminus Flux	Current		Dimmable
LED.362	REFLED SUPERIA MR16	GU5.3	8W	50W	12V	2700K	621lm	952mA	40°	NO
LED.363	REFLED SUPERIA MR16	GU5.3	8W	50W	12V	3000K	621lm	952mA	25°	NO
LED.277	REFLED SUPERIA MR16	GU5.3	8W	50W	12V	3000K	621lm	952mA	40°	NO
LED.364	REFLED SUPERIA MR16	GU5.3	8W	50W	12V	3000K	621lm	952mA	60°	NO
LED.365	REFLED SUPERIA MR16	GU5.3	8W	50W	12V	4000K	621lm	952mA	40°	NO

