




60LED/m WW BENDABLE

Flexible LEDs 

Monochromatic: Management through:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
 - Wireless IR & RF control units.
 - DALI Protocol devices.
- Bendable LED Strip ideal for demanding applications.



Code	No.LED	Colour	Watt	Dimensions	Reel	Colour Temperature /CRI	Luminus FLUX (LM)	Voltage		 **	 IP
TIV.255	60/m	WARM WHITE	4.8W/m	8x1.8mm	5m	2900-3100K / CRI80+	430lm/m	12VDC	120°	50mm	IP20
TIV.256	60/m	NEUTRAL WHITE	4.8W/m	8x1.8mm	5m	4000-4300K / CRI80+	570lm/m	12VDC	120°	50mm	IP20

* Please confirm the connection points on the modules.





60LED/m VARIABLE ANGLE

RGB: Management through:

- DMX 512 controllers.
- Wireless IR & RF control units.
- DALI Protocol devices.

Monochromatic: Management through:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Strip with variable angle of LEDs for demanding applications.



RGB

Code*	No.LED	Colour	Watt	Dimensions	Reel	Voltage	Beam Angle	Cuttable**	IP
TIV.259 /CA	60/m	RGB	14.4W/m	16.5x2mm	5m	24VDC	120°	100mm	IP20


*CA= Common Anode

** Please confirm the connection points on the modules.


Monochromatic

Code	No.LED	Colour	Watt	Dimensions	Reel	Colour Temperature /CRI	Luminous FLUX (LM)	Voltage	Beam Angle	Cuttable*	IP
TIV.257	60/m	WARM WHITE	4.8W/m	14.5x2mm	5m	2900-3100K / CRI80+	430lm/m	24VDC	120°	100mm	IP20
TIV.258	60/m	NEUTRAL WHITE	4.8W/m	14.5x2mm	5m	4000-4300K / CRI80+	570lm/m	24VDC	120°	100mm	IP20

* Please confirm the connection points on the modules.



RGB



Monochromatic